



Product Data

Transmax Dual Multivehicle

Dual Clutch Fluid

Description

Castrol Transmax Dual Multivehicle is a full synthetic dual clutch transmission fluid formulated with Smooth Drive Technology™. This product is suitable for use in the majority of dual clutch transmissions in the global car parc. Transmax Dual Multivehicle's low viscosity formulation also offers the potential to deliver fuel economy benefits.

Advantages

- Enhanced friction durability for smooth transmission performance
- Improved wear protection to provide longer component life
- Excellent thermal and oxidative stability to effectively resist oxidation
- Excellent synchroniser and clutch performance due to balanced frictional characteristics
- High shear resistance - constant viscosity during oil life Proven performance in field trials

Typical Characteristics

Name	Method	Units	Transmax Dual Multivehicle
Density @ 15C, Relative	ASTM D4052	g/ml	0.848
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s (cts)	5.4
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s (cts)	25
Viscosity Index	ASTM D2270	None	163
Viscosity, Brookfield @ -40°C (75W)	ASTM D2983	mPa.s (cP)	7200
Pour Point	ASTM D97	°C	-54
Flash Point, COC	ASTM D92	°C	190

Product Performance Claims

Suitable for use in 6 speed dual clutch transmissions from Ford

Nissan

Renault

VW group

Volvo

Suitable for use in 7 speed dual clutch transmissions from BMW

Ford

MB

Nissan

Renault

and VW group.

Suitable for use where the following are called for: Ford WSS-M2C-936-A

VW/Audi TL52529 (G 052 529)

VW/Audi TL52182 (G 052 182)

VW/Audi TL55529 (G 055 529)

Volvo 1161838

Volvo 1161839

BMW DCTF-1

DCTF-2

BMW 88 22 0 440 214

BMW 82 22 2 147 477

BMW 83 22 2 148 578

BMW 83 22 2 148 579

BMW 83 22 2 167 666

BMW MTF LT-5

MB 236.22

MB 236.21

MB 236.24

PSA 9734.52

Pentosin FFL-3

Porsche Oil No. 999.917.080.00

Jaguar / Land Rover GX73-M1R564-AA

Mitsubishi MZ320065

Dia-Queen SSTF-1.

Transmax Dual Multivehicle

01 Feb 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com