











TOTAL QUARTZ INEO FIRST 0W-20

Engine oil

KEY DATA

LIGHT VEHICLE RANGE



INTERNATIONAL STANDARDS

✓ ACEA C5

PETROL & DIESEL MOTOR OIL

SAE 0W-20

SYNTHETIC TECHNOLOGY

FUEL ECONOMY & LOW SAPS

MANUFACTURER APPROVALS

✓ PSA PEUGEOT CITROEN B71 2010

DESCRIPTION

Nowadays, engines face tremendously high operating temperatures and pressures. This accelerates oil oxidation and destabilizes its molecular structure, leading to increased friction and sludge build-up

TOTAL QUARTZ INEO FIRST 0W-20 with ART (Age Resistance Technology) is an advanced, highly charged formula which fortifies the anti-oxidation properties of the engine oil offering therefore **ultimate protection** against sludge formation and wear.

TOTAL QUARTZ with ART,

Keep your engine younger for longer.

APPLICATIONS

TOTAL QUARTZ INEO FIRST 0W-20 is synthetic engine oil, formulated and used for PSA PEUGEOT CITROEN's factory fill and after sales.

This pollution-control synthetic engine oil provides engines with the best possible protection against wear and clogging. The post-treatment systems, sensitive to the lubricants used and expensive to maintain, are also protected over the long-term thanks to the "Low SAPS" formulation (low content of sulphated ash, phosphorus and sulphur contents).

Using this engine oil can help generate fuel savings without the need to change driving style. It is also suitable for the most demanding driving conditions (door-to-door, sports driving, repeated start-ups, city and motorway driving, etc.)

TOTAL QUARTZ INEO FIRST 0W-20 is particularly well-suited for use with recent engines of PSA (DV5R and EB2DT), and particularly ones equipped with BLUE HDi, PureTech using Stop & Start technologies, and hybrid engines which require new-generation engine oils.

CUSTOMER BENEFITS

- Reduced environmental impact: Fuel savings of 3.7% as measured by the official M111 FE test. It guarantees
 compliance with all the performance levels claimed by PEUGEOT and CITROËN in relation to environmental
 standards.
- Protection for pollution-control systems: This engine oil optimises the way in which three-way catalytic converters
 and particulate filters operate, preventing them from getting clogged up with soot or sludge deposits. This reduces
 particulate emissions, NOx, HC and CO in particular.
- **Engine protection and cleanliness:** This oil offers the best possible protection in its category against wear and clogging as soon as the engine is started up.
- Easier cold starts: The 0W-20 grade, together with special additives, makes cold engine starts easier, even at very low temperatures (validation tests carried out down to -40°C)
- **Oil change intervals:** TOTAL QUARTZ INEO FIRST 0W-20 retains all of its properties, in accordance with the service plans recommended by PEUGEOT and CITROËN.

CHARACTERISTICS*

Test	Unit	Test method	Result
Viscosity grade	-	SAE J300	0W-20
Density at 15°C	kg/m³	NF EN ISO 12185	841
Kinematic viscosity at 40°C	mm²/s	ISO 3104	43.5
Kinematic viscosity at 100°C	mm²/s	ISO 3104	8.3
Viscosity index	-	ISO 2909	170
Pour Point	°C	NF T 60 105	-48
OC Flash Point	°C	NF EN ISO 2592	232

^{*}The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Recommendations for use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Health, safety and the environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

TOTAL LUBRIFIANTS – Immeuble Spazio 562, avenue du Parc de l'île 92029 Nanterre cedex France

TOTAL QUARTZ INEO FIRST 0W-20

Last update of this datasheet: 10/2018

